

RP RABINE EQUIPMENT (586) 949-3320

Black Neptune™

Smooth, chemical resistant cover designed to work as hard as you.

3000 PSI

- 1 Wire Braid
- 250°F maximum
- MPT solid & swivel ends
- Black Bend Restrictors



Part	Size	Wt.
1016	1/4x15'	3 lb
2547	1/4x25'	4 lb
2546	1/4x30'	5 lb
2544	1/4x50'	8 lb
3036	1/4x100'	16 lb
4915	3/8x15'	4 lb
4353	3/8x25'	6 lb
3601	3/8x30'	8 lb
1208	3/8x50'	13 lb
1459	3/8x75'	19 lb
1457	3/8x100'	25 lb
4309	3/8x150'	31 lb
1025	1/2x25'	9 lb
1113	1/2x50'	18 lb
3733	1/2x100'	35 lb

4000 PSI

- 1 wire braid
- 250°F maximum
- MPT solid & swivel ends
- Orange Bend Restrictors



200', 250', 300' hoses have swivels on both ends

Part	Size	Wt.
6874	3/8x25'	7 lb
6875	3/8x30'	9 lb
6867	3/8x50'	13 lb
6868	3/8x75'	19 lb
6869	3/8x100'	26 lb
6870	3/8x150'	39 lb
6871	3/8x200'	52 lb
6872	3/8x250'	65 lb
6873	3/8x300'	78 lb

Black Neptune™ 4500 PSI

- 2 Wire Braid
- 250°F maximum
- MPT solid & swivel ends
- Red Bend Restrictors



Part	Size	Wt.
4923	3/8x15'	5 lb
4352	3/8x25'	8 lb
1207	3/8x50'	15 lb
4221	3/8x75'	21 lb
1458	3/8x100'	28 lb
4302	3/8x150'	35 lb

6000 PSI

Part	Size	Wt.
6165	3/8x50'	16 lb
6173	3/8x100'	32 lb

Custom Cut Hoses

Part	Size	PSI
4062	1/4" (Increments of 25')	3000
4220	3/8"	3000
3693	3/8"	4000
4159	3/8"	4500
4210	1/2" (increments of 25')	3000

Custom Cut Fittings

Part	Product
3048	1/4 hose x 1/4" MPT Solid fitting
3049	1/4 hose x 1/4" MPT Swivel fitting
3050	3/8 hose x 3/8" MPT solid fitting
3051	3/8 hose x 3/8" MPT swivel fitting
3726	1/2 hose x 1/2" MPT solid fitting
3727	1/2 hose x 1/2" MPT swivel fitting
2887	1/4" Black bend restrictor
2532	3/8" Black bend restrictor
2531	3/8" Red bend restrictor
5013	3/8" Orange Bend Restrictor
3912	1/2" Black Bend Restrictor

Full Roll Hoses (No fittings)

- Reels of hose could have as many as 3 cuts per roll.
- No piece will be smaller than 50'

Part	Size	PSI	Wt.
2894	1/4x500'	3000	86 lb
2529	3/8x500'	3000	130 lb
6713	3/8x500'	4000	130 lb
4158	3/8x450'	4500	138 lb
4208	1/2x500'	3000	176 lb



Blue Neptune™

Non-Marking
3000 PSI

- 250°F. maximum
- MPT solid & swivel ends
- Black Bend Restrictors

Part	Size	Wt.
5921	1/4x25'	7 lb
5279	1/4x50'	13 lb
5280	1/4x100'	18 lb
4515	3/8x25'	9 lb
1205	3/8x50'	13 lb
3296	3/8x75'	18 lb
3297	3/8x100'	25 lb
4516	3/8x150'	31 lb



4500 PSI

- 2 Wire braid
- 250°F. maximum
- MPT solid & swivel ends
- Red Bend Restrictors

Part	Size	Wt.
5567	3/8x15'	5 lb
5230	3/8x25'	7 lb
5432	3/8x50'	13 lb
5032	3/8x75'	18 lb
5033	3/8x100'	25 lb
5034	3/8x150'	31 lb

Custom Cut Hoses

Part	Size	PSI	Length
3445	1/4"	3000	Foot
4061	3/8"	3000	Foot
2393	3/8"	4500	Foot

Custom Cut Fittings

Part	Product
3048	1/4 hose x 1/4"MPT Solid
3049	1/4 hose x 1/4"MPT Swivel
3050	3/8 hose x 3/8"MPT solid
3051	3/8 hose x 3/8"MPT swivel
2887	1/4" Black bend restrictor
2531	3/8" Red bend restrictor

Full Roll Hoses

Part	Size	PSI	Length
1669	1/4"	3000	500'
3295	3/8"	3000	500'
5036	3/8"	4500	450'

Gray Neptune™ 4000 PSI



Non-Marking

- 1 Wire Braid
- Smooth Cover
- 250°F. maximum
- MPT solid & swivel ends
- Orange Bend Restrictors

Part	Size	Wt.
5908	3/8x25'	9 lb
5872	3/8x50'	13 lb
5873	3/8x100'	26 lb
6783	3/8x150'	38 lb

Custom Cut Hoses

Part	Size	PSI
4220	3/8"	4000

Custom Cut Fittings

Part	Product
3050	3/8 hose x 3/8"MPT solid fitting
3051	3/8 hose x 3/8"MPT swivel fitting
5013	3/8" Orange Bend Restrictor



SpiraFlow™

Specifically designed for the Pressure Washer Industry

- Spiraflow™ is ridged every 6 inches to prevent it from laying flat on the ground.
- SpiraFlow™'s ridges conveniently channel cleaning chemicals and water under the hose to prevent damming.
- Spiraflow™'s durable spiral surface provides a reliable indicator of wear from abrasion.



- 4000 PSI single wire
- 250°F maximum
- Male solid/swivel fittings
- Orange bend restrictors

Elevates hose to keep water flowing right under it

Blue Non-Marking

Part	Length	Cover
5231	3/8 x 50'	Blue
6281	3/8 x 100'	30 lb
6282	3/8 x 150'	45 lb
6283	3/8 x 200'	60 lb

Grey Non-Marking

Part	Length	Cover
6589	3/8 x 50'	15 lb
6593	3/8 x 100'	30 lb
6654	3/8 x 150'	45 lb
6655	3/8 x 200'	60 lb

Wrapped Cover Hoses

- Lighter than standard hoses
- Greater bend radius
- Non slip finish on cover
- Male solid and swivel fittings
- 310°F maximum**
- Orange** bend restrictors 4000 PSI
- **Red** bend restrictors 5800 PSI



Part	Size	PSI
5848	3/8x50' R1	4000
5849	3/8x100' R1	4000
4907	3/8x50' R2	5800
4908	3/8x100' R2	5800

Blue Wrapped Non-Marking

- Lighter than standard hoses
- Greater bend radius
- Non slip finish on cover
- Male solid and swivel fittings
- 310°F maximum**
- Orange** bend restrictors 4000 PSI

New in 2009



Part	Size	PSI
5857	3/8x50' R1	4000
5860	3/8x100' R1	4000

Whip/Connector Lines

Whip lines are made from ends of rolls or bulk boxes, can be black, blue, or grey.



Part	Size	PSI
3030	3/8x2'	3000
3281	3/8x3'	3000
3031	3/8x4'	3000
4230	3/8x5'	3000
3032	3/8x6'	3000
3033	3/8x8'	3000
5830	3/8x2'	4000
5893	3/8x3'	4000
5894	3/8x4'	4000
5907	3/8x5'	4000
5362	3/8x6'	4000
5566	3/8x8'	4000
6497	3/8x10'	4000
1693	3/8x2'	4500
4311	3/8x3'	4500
1204	3/8x4'	4500
3319	3/8x5'	4500
1203	3/8x6'	4500
1202	3/8x8'	4500

1/4" Hobby Hoses

Oil Resistant Synthetic Rubber

High pressure replacement hoses for home owner type machines manufactured by DeVilbiss, Generac/Briggs, Karcher, and others



2600 PSI maximum

Part	Size	Fittings
2188	1/4"x25'	22x1/4FBSP
6018	1/4"x25'	22x22mm
6125	1/4"x30'	22x22mm

GOODYEAR Whitewater® Combo

For pressure washers and steam machines

- MPT solid fittings
- Grip Black bend restrictor
- No bend restrictor on 1/2"

Steam max 325° @ 350 PSI
Hot water max 250° @ 3000 PSI
1/2" hose max 250° @ 2500 PSI

Part	Size	Wt.
4891	3/8x25'	7 lb
1201	3/8x50'	13 lb
1553	3/8x100'	24 lb
1460	1/2x50'	18 lb



GOODYEAR Flexsteel® 250 CB Steam

- 250 PSI maximum
- 450°F. maximum
- 1/2" ID (12.7mm)
- 1.06" OD (26.9mm)



Part	Product
3431	25' w/boss clamp
3188	50' w/boss clamp

GOODYEAR Insta-Grip 250™

Designed for use with push on fittings. Gives installation a more professional appearance.

- 250 PSI maximum
- 212°F. maximum

Part	ID
4016	1/4"
3655	3/8"
4017	1/2"
4964	5/8"
4965	3/4"





Sewer Hoses



Durable thermoplastic construction is flexible and light weight for cornering around line elbows. Smooth surface cover allows easy access through drain pipes and sewer lines

Part	ID	PSI	Length	Temp
2560	1/8"	2900	50'	140°
2561	1/8"	2900	100'	140°
6217	1/4"	4350	50'	212°
6215	1/4"	4350	100'	212°



Pulse Hose

- 1500 PSI maximum
- 250°F. maximum

One end must be plugged

Part	Product
2499	24" Hi-flex 3/8" MPT x 3/8" FPT
2500	24" Hi-flex 3/8" MPT x plugged

GOODYEAR Spiraflex® 1500



General purpose water suction and discharge hose for use in industrial, agricultural, construction cleanup.

- Long wearing and abrasion resistant
- Flexible and crush resistant
- 158° F. maximum

Part	ID	Length	PSI
3754	3/4"	100'	100
4011	1"	100'	100
4015	1 1/2"	20'	100
3138	1 1/2"	100'	100

Reusable Hose Couplers



- Extend the life of damaged hoses
- Easy to repair in the field
- No crimps required
- 3,000 to 4500 PSI

Part	Product	Hose OD
2015	3/8" MPT solid reduced OD	.62
2016	3/8" MPT swivel reduced OD	.62
6037	Gates 3/8" MPT solid reduced OD	.62
6048	Gates 3/8" MPT swivel reduced OD	.62
2017	3/8" MPT solid	.62
2018	3/8" MPT swivel	.692
6054	Gates solid 3/8" MPT	.68-.70
3110	Gates swivel 3/8" MPT	.68-.70



Clear Vinyl Tubing

Part	Product
2288	1/4" ID 100' roll

Clear Polybraided Tubing



Part	ID	Roll
2903	1/4"	25'
2904	1/4"	50'
2905	1/4"	100'
6327	1/4"	300'
2906	3/8"	25'
2907	3/8"	50'
2908	3/8"	100'
6208	3/8"	300'
2909	1/2"	25'
2910	1/2"	50'
2911	1/2"	100'
2915	5/8"	25'
2916	5/8"	50'
2917	5/8"	100'
2912	3/4"	25'
2913	3/4"	50'
2914	3/4"	100'



Hose Clamps

- Stainless Steel band
- 10 clamps per box

Part	Size	Band	Diameter
1495	#04	5/16" micro	1/4"-5/8"
1496	#06	5/16" micro	5/16"-7/8"
1499	#06	1/2"	3/8"-7/8"
1500	#08	1/2"	7/16"-1"
1501	#10	1/2"	1/2"-1-1/8"
1502	#12	1/2"	1/2"-1-1/4"
1556	#20	1/2"	3/4"-1-3/4"
3599	#24	1/2"	1"-2"

Plastic Cable Ties



Part	Size	Color	Qty
1782	4" x .10	Natural 18#	100
1785	8" x .19	Black 40#	100
1789	11" x .18	Black 50#	100
1788	11" x .18	Natural 50#	100
4372	14" x .18	Natural 50#	100
5636	15" x .30	Natural 120#	100
5637	24" x .34	Natural 175#	50