

RP RABINE EQUIPMENT (586) 949-3320

WINGO Generators

Industrial designed, rugged, two bearing generator. Units are designed to rotate either direction without changing the wiring.

Require approximately 2HP input for each 1000 watts output from the generator

Each unit is tested at the factory to insure its performance and reliability.

- 2000 watts
- 3600 RPM
- Shaft diameter: 5/8"
- Motor starting cap: 1/2hp
- Receptacles 120v
- Volts @ 60hz: 120
- Rated AC amps: 16.7
- Weight: 59 lbs.



Part	Product
3935	2SFM2PC-1AC generator
2441	23607 AC brush (3 required)
2446	41171 capacitor (2 required)
2433	55223 bearing 6203-2RS
2448	64640-000 fan
2442	91452 rectifier

Maintenance Meter

For 1 or 2 cylinder gasoline engines. Use to perform regular preventive maintenance. Benefit with increased fuel economy, less down time, and longer engine life.



3 FUNCTIONS:

- Hour Meter:** records actual running time of engine. Non-erasable.
- Service Alert:** Warns of need of lube & oil change in 25 hour intervals. Will flash for 2 hours while engine runs.
- Tachometer:** Displays RPM is running up to 9,000 RPM.

Part	Product
4188	Maintenance meter

Engine Throttle Control

Save wear and tear on pump and engine. Reduce engine speed in bypass mode. Returns to full operating RPM immediately when pump operation resumes.



3/8" MPT inlet
36" cable

Part	Product	PSI
4723	Z Speed Throttle Control Kit	3000
1660	Throttle Control Kit	5000

Ground Faults (GFCI)

Ground Fault Circuit Interrupters are fast acting circuit breakers which sense small imbalances in the circuit caused by current leakage to the ground, and in a fraction of a second shuts off the electricity.

User Attachable right Angle

- NEMA5-15P
- Accepts cord SJT to 12 AWG
- Outdoor rated
- UL & CSA approved

Part	Product
2291	120v/15amp
3593	125v/20amp



Shock Shield User Attachable

- 120v or 240v applications
- 20 amp protection 120v & 240v
- No switches or wires to change automatically senses input voltage
- UL & CSA approved
- 2 tube sealant included

Part	Product
2293	25000 GFCI



Right Angle Plug

Ideal for construction site and industrial maintenance projects UL/CSA approved. Will comply with OSHA regulations Rugged design indoor/outdoor



- 36 FT 14/3 SJTW cable
- 120v 15 amp

Part	Product
3072	

Heavy Duty In-Line Cord

- Outdoor rated
- UL & CSA approved
- NO PLUG ON 220 volt cords



Part	Product
5549	110v/15amp 36' cord
5550	110v/20amp 36' cord
3689	220v/30amp 25' cord

RP RABINE EQUIPMENT (586) 949-3320



Please pay attention to RPM, voltage ratings and shaft size. If you are not sure ask for assistance while ordering

For pressure washers, steam cleaners, portable and self contained stationary systems for direct drive pumps. All motors thoroughly tested at the factory and carefully packaged for shipment. Proper ventilation for the motor must be provided. Obstructed airflow can lead to reduction of motor life

Single Phase, Rigid Base, C-Face Open Drip Proof (ODP)

- Ball bearing design
- Manual thermal overload in conduit box
- UL & CSA recognized component approval
- 200°C. copper windings

For direct drive

Intended for use indoors where atmosphere is relatively clean, dry, well ventilated and non-corrosive



Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
2548	PCL1319M	5/8"	56C	1.5	1725	115/230	14/7	46
2549	PCL1313M	5/8"	56C	1.5	3450	115/230	13/7	38
2550	PCL1322M	5/8"	56C	2.0	1725	115/230	18/9	48
2551	PCL1317M	5/8"	56C	2.0	3450	115/230	17/8.8	45
2552	CL1408TM	1-1/8"	184TC	3.0	1725	115/230	32/16	82
2553	PCL1326M	5/8"	56C	3.0	3450	230/208	13/12	50
2554	PCL1327M	5/8"	56HCY	5.0	3450	230	23	58
3329	Special	3/4"	56C	5.0	3450	230	23	58
2555	CL1410TM	1-1/8"	184TC	5.0	1725	230/208	25/23	91

Single Phase, Rigid Base, C-Face Totally Enclosed, Fan Cooled (TEFC)

May be installed where dirt, moisture, or dust are present and in outdoor locations.

For direct drive



Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
3122	PCL3514M	5/8"	56C	1.5	1725	115/230	12/6	53
3121	PCL3513M	5/8"	56C	1.5	3450	115/230	13/7	41
3123	PCL3515M	5/8"	56C	2.0	3450	115/230	18/9	46
3126	CL3619TM	1-1/8"	184TC	3.0	1725	230	13.2	84
3125	PCL3519M	5/8"	56C	3.0	3450	230/208	13/12.5	55
3128	CL3612TM	1-1/8"	184TC	5.0	1725	230	23	104
3127	CL3608TM	1-1/8"	184TC	5.0	3450	230	19.5	94

3 Phase TEFC Motors

C-Face for direct drive units

Ball bearings with a locked drive end bearing, dynamically balanced rotor and heavy gauge steel frame.

For pumps, fans, conveyors, gear reducers or other applications requiring a NEMA C-face motor.

Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
2664	CM3615T	1-1/8"	184TC	5.0	1725	208/230/460	13/14/7	81

Rigid Base for Belt Drive units

- Pumps, compressors, fans, conveyors, and other general purpose 3 phase applications.
- Suitable for mounting in any positions
- Ball bearings, heavy gauge steel frames and gasketed conduit boxes
- EM motors have NEMA Premium® efficiency and 3 year warranty

Part	Baldor	Shaft	Frame	HP	RPM	Voltage	Amps	Wt.
5251	EM3770T	1-3/8"	213T	7.5	1760	230/460	25/12.5	176
5252	EM3774T	1-3/8"	215T	10.0	1760	230/460	25/12.5	204