

RP RABINE EQUIPMENT (586)949-3320

SUTTNER ST-1100 Lightweight



Perfect for cold water units in factories and plants or smaller hot water units

- 8 GPM maximum
- 3000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

No Repair Kit

Part	Model
4126	ST-1100

SUTTNER ST-810 Front Entry

For car wash, fleet wash and truck wash operations.

Front inlet design keeps dirty hose just far enough away, keeping the operator clean. Heavy duty valve.



- 8 GPM maximum
- 3050 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
1479

MTM407



- 7 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

New in 2009

Part
6150

MV2005



- 8 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8FPT inlet
- 1/4FPT outlet

Part	Model
6110	MV2005
6109	Kit

SUTTNER ST-1500 Top Seller

Well suited for a variety of industrial washing applications. Streamline designed to be "universally" comfortable, even for very small hands.



Stainless steel internal tubing, brass inlets and outlets

- 12 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1475	ST-1500
1528	Kit

ST-1500 Weep Gun



ST-1500W weep allows water to continue flowing after trigger is released. This prevents gun freeze

Part	Model
2324	ST-1500W
1528	Repair kit

SUTTNER ST-1500H Open Gun

Specialty use gun

Ideal when unloader is unavailable or for manual start pressure washer.



- 12 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1291	ST1500H

ST-2000 Big Hand Gun

Ideal for rental machines
Designed for heavy duty durability. Takes the heat and abuse.
Easy access to replace cartridge valve.



- 12 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1477	ST-2000
1528	Repair kit

YRL51 Gun



- 13.2 GPM maximum
- 4050 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6267

5030 Gun



- 12 GPM maximum
- 4500 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1740	5030
1733	Kit

RP RABINE EQUIPMENT (586)949-3320



AL35

Easy pull trigger even at 5000 PSI!

- 8 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" brass inlet
- 1/4" discharge



Part	Model
6522	AL35
6524	Kit

VEGA/YG4000 Spray Gun

Ergonomic designed hand guard
Easy trigger pull

- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
3452	VEGA
3453	Kit



Spray Guns

Excellent choice for heavy industrial applications.

- 10 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model	Outlet
1480	21250B	SS
2341	21290C	Brass
1632	Repair kit	



RL30/YG5000 Gun

Trigger design for easier pull at higher pressures
Larger, more comfortable hand grip space to accommodate gloves

- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
4855	RL30/YG5000
6228	Repair kit

DG5000 Spray Gun

- 10 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part
6906

ST-2305 Easy Pull!!

The SUTTNER exclusive trigger, ideal working long hours.
Reduces trigger opening force by up to 50% compared to all other rear entry spray guns.

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
4654	ST-2305
4540	Repair kit

ST-2605 Relax Action

True over center cam
Easiest opening and holding trigger.
SUTTNER exclusive trigger ideal for working long hours.
Reduces trigger force up to 20% holding force up to 60%

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
4539	ST-2605
4540	Repair kit

KEW Style Spray Gun

With bayonet coupler and plug on outlet

- 10 GPM maximum
- 5000 PSI maximum
- 300°F max
- 1/4" FPT outlet



Part	Model
6707	KEW w/coupler & plug
6123	Coupler replacement
6140	Plug replacement

Karcher Style Spray Gun

22mm inlet and discharge.

- 7 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part
6069

Spray Guns

RP RABINE EQUIPMENT (586)949-3320

Chemical Resistant Guns

SUTTNER ST-810 POM



Front entry gun is the best chemical application gun with a stainless steel spring, needle, ball and a poly seat for chemical resistance

- 8 GPM maximum
- 2000 PSI maximum
- 320°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6561

ST-2315 w/Ceramic Ball

New in 2009

Ceramic ball in valve is highly resistant against nearly all soaps and acids.



Suttner exclusive "relax-action trigger and comfort grip reduces trigger force up to 40% and holding force up to 90%
Unitized valve for easy repair

- 27 GPM maximum
- 2170 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6916

YG5000C Gun

With ceramic ball for use with chlorine & acid



- Ceramic ball for excellent corrosion resistance
- Forged brass body with stainless wetted parts
- Trigger lock to prevent accidental activation
- Comfortable impact resistant housing

- 10.5 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6418	YG5000C
6425	Repair kit

Stainless Steel Guns

New in 2009

SUTTNER ST-3300



Replaces ST-3002.
Highest volume rated industrial gun.

- Forged stainless steel housing, piston, and malleable seat.
- Special heat and chemical resistant seals

- 27 GPM maximum
- 2170 PSI maximum
- 300°F. maximum

Part
6708

- 1/2" FPT inlet
- 1/2" FPT outlet

SUTTNER ST-2700



- Stainless steel internal components.
- Suitable for corrosive chemical usage
- "Relax action" trigger and comfort grip reduces trigger force up to 20%
- Unitized valve for easy repair

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4730	ST2700SS
5609	Repair kit

New in 2009

ST-3600 Gun

Suttner's highest pressure rated industrial gun.



- Forged stainless steel housing, piston, and malleable seat.
- Special heat and chemical resistant seals
- 21 GPM maximum
- 8700 PSI maximum
- 300°F maximum
- 1/2" FPT inlet
- 1/2" FPT outlet

ST-3600 Lance

- Perfect fit for the ST-3600 gun.
- Stainless steel construction is ideal for chemical applications
- Adjustable handle



- 1/2" FPT inlet
- 1/4" FPT outlet

Part	Product
6714	Gun
6732	Lance

Linear/Straight Guns

SUTTNER ST-601

Heavy duty impact trigger guard has made ST-601 an industry standard for telescopic wand manufacturers.

Ideal for cleaning vertical & overhead surfaces.



- 12 GPM maximum
- 4000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
2396	ST-601
1528	Repair kit



YG4000S

Straight spray gun. Insulated handle remains cool at maximum fluid temperature

- 10.5 GPM maximum
- 3650 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
3451	YG4000S
3450	Repair kit

RP RABINE EQUIPMENT (586)949-3320

High Volume, Low Pressure Guns

SUTTNER ST2620

For high volume, low pressure machines!

Hold trigger open with one finger
Relax action trigger reduces hand fatigue
Easiest opening & holding trigger in class
Proper spray angle for optimum position

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Part
6936	ST2620
4540	Repair Kit

ST2720 Stainless Steel

Ideal for high volume, low pressure applications such as farms, chemical or food processing industries!
Stainless steel valve components create a durable, long lasting gun

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Part
6937	ST2720
5609	Repair Kit

YG1732 Heavy Duty Gun

- Shockproof plastic housing
- Construction of stainless steel & brass
- Ergonomic construction
- Trigger operation minimizes fatigue

- 32 GPM maximum
- 1740 PSI maximum
- 320°F maximum

- 1/2" FPT inlet
- 1/2" FPT outlet



Part
3481

MV2005 w/Molded Grip Lance

Quick connect plug on inlet
Lance extension w/ quick connect socket on outlet



- 8 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6843	With 24" mg lance
6273	With 36"mg lance
5889	With 48" mg lance

Hobby Hose, Gun, Lance Kits

Ideal hose, gun and lance combinations replacement for low pressure machines sold in various retail outlets

- 1/4"x22mmx22mm hose
- Trigger gun w/one piece molded 12" extension
- 18" wand pipe extension
- 22mm gun inlet & outlet
- 6.6 GPM maximum
- 2600 PSI maximum



Part	Product
6132	Kit w/QC outlet
5418	Kit w/hilo nozzle
6081	Lance w/hilo nozzle

RLW40 Dump Gun

Excellent for car washes. Water continues to run through tube when gun trigger released, preventing freeze up in cold weather.



- 10.5 GPM maximum
- 3050 PSI maximum
- 140°F maximum
- 3/8FPT inlet
- 1/8FPT outlet

NOTE: Trigger will not pull unless under pressure

Part	Model
1046	16"
2375	40"
2376	Repair kit

Plastic Low Pressure Guns

To be used for chemical pre spray, or to spray acids.

- 2 GPM maximum
- 150 PSI maximum
- 100°F maximum



Part	Model
4494	Spraying system 1/4" FPT inlet
1633	Spraying Systems 3/8" hose barb inlet
6781	HPC 3/8" hose barb inlet
2201	Cone jet angled assembly (4494, 1633)

Rear Entry Gun w/Extension

- One piece
- 22mm outlet
- 6.5 GPM maximum
- 3200 PSI maximum
- 195°F maximum



Part	Model
6788	3/8" MPT Inlet
6737	22mm Male Inlet

Lances

RP RABINE EQUIPMENT (586)949-3320

Bent Lance Adapter

17° Angle



Eliminate the need to stock straight and bent lances. Thread the Bent Lance Adapter on the outlet of your lance and it becomes a bent lance. Remove the adapter for straight lance usage.

Part	Product
5347	Adapter 1/4ft x 1/4ft
4934	Adapter 1/4ft x 1/4mpt

Wand Saver



1/4 inset connector with quick change plug. When used to connect wand to gun will help prevent breaking threads.

Part	Product
6461	Wand Saver

Freight Saver Lance Extender

Extend a lance to any length with this nickel plated lance collar. Threads are inset to make lance less prone to breakage and give greater leverage under pressure. (Example: turn a 36" lance into a 72" lance by connecting two 36" wand pipes or molded grip lances.)



Part
6362



Round Molded Grip

- Heavy duty round grip ergonomic comfort
- 1/4" MPT pipe
- 4000 PSI



Part	Size
6288	12" Plated Steel
6543	18" Plated Steel
6289	24" Plated Steel
6290	36" Plated Steel
6333	40" Plated Steel
6291	48" Plated Steel
6198	59" Plated Steel
6201	79" Plated Steel
6297	24" Stainless Steel
6298	36" Stainless Steel
6299	48" Stainless Steel
6084	59" Stainless Steel
6085	79" Stainless Steel

SUTTNER Star Shape Grip

Threads are rolled on and not cut, creating superior strength and consistent sealing.

Linear Aeration™ provides continuous air flow through the "star-shape grip, for a cooler handle.

Conforms to the curvature of the hand while allowing the hand to comfortably change positions



- 1/4" pipe
- 5800 PSI maximum
- 10.5 GPM maximum
- 300°F maximum

Part	Size
5853	12" ST007 steel zinc plate
1713	24" ST007 steel zinc plate
1714	36" ST007 steel zinc plate
1716	48" ST007 steel zinc plate
1717	59" ST007 steel zinc plate
1718	79" ST007 steel zinc plate
6821	36" ST002 stainless steel
6822	48" ST002 stainless steel



Square Molded Grip

- 1/4" MPT Zinc plated pipe
- Square molded grip
- 4500 PSI maximum



Part	Size
1398	12" Zinc
5447	24" Zinc
1401	36" Zinc
1402	48" Zinc
1657	59" Zinc
1403	79" Zinc
1658	36" SS
1659	48" SS

ST-85 Push & Pull lance

For hard to reach applications, such as gutters.

Can be angled to 90°

Each desired angle remains stationary until adjusted



- 34" long stainless steel
- 3050 PSI maximum
- 300°F maximum
- 1/4" MPT I/O

Part	Product
6823	ST-85 lance

RP RABINE EQUIPMENT (586)949-3320



Vented Grip

Vented grip allows air to pass over the pipe to dissipate heat.



- 10.5 GPM maximum
- 300°F maximum
- 4100 PSI maximum
- 1/4" pipe

Part	Size
6767	18" Zinc Plate Steel
6768	24" Zinc Plate Steel
6769	36" Zinc Plate Steel
6770	48" Zinc Plate Steel
6771	59" Zinc Plate Steel
6772	79" Zinc Plate Steel
6773	24" Stainless Steel
6774	36" Stainless Steel
6775	48" Stainless Steel
6776	59" Stainless Steel
6777	79" Stainless Steel



Vented Grip

Vented grip allows heat to dissipate providing a cooler handle. Easily adjusts anywhere on lance for ergonomic positioning.

- Zinc plated steel
- 300°F maximum
- 5800 PSI maximum
- 1/4" MPT inlet & outlet



Part	Size
3570	24"
2162	36"
2163	48"

Lance Grips

Molded grip can be used with 1/4" non insulated wand pipe to make molded grip lances. Screws included

Part
2276



Make your own vented grip lances!

Part
2167



Lance Side Handle

Slide over 1/4" non-insulated wand pipe or screw into a vented grip, or use C-clamp style to slide over and tighten onto lance



Part	Product
1536	Slide over
4886	C-clamp



C-clamp

Non Insulated Pipes

•1/4" MPT

Part	Size
1520	12" Plated Steel
4698	18" Plated Steel
3378	24" Plated Steel
1745	36" Plated Steel
2158	48" Plated Steel
2159	59" Plated Steel
2160	79" Plated Steel
4513	24" Stainless Steel
2277	36" Stainless Steel
4514	48" Stainless Steel
3248	59" Stainless Steel
2345	79" Stainless Steel
6462	24" Aluminum
6463	36" Aluminum
6464	48" Aluminum
6465	59" Aluminum
6372	79" Aluminum

Deluxified dual lances equipped with a quick connect plug on inlet, quick connect socket on high pressure outlet and soaper nozzle on low pressure outlet



SUTTNER

Dual Lances

For use when high and low pressures are needed, i.e., spraying cleaning agents with low pressure through an injector valve and then cleaning with high pressure.

- 38" long
- 300°F maximum
- Brass soap nozzle
- 1/4" MPT inlet
- 10.5 GPM maximum
- 1/4" FPT outlets



ST53

ST-54 protective lip on side handle. Stainless steel internal adjustment rod for longer life. Protective valve cover for added safety



ST54

Part	Product	PSI
1699	ST-54	4500
4392	ST-54 Deluxified	4500
2326	ST-53	4000
4503	ST-53 Deluxified	4000
3469	ST-54 Repair kit	
4243	ST-53 Repair kit	

RP RABINE EQUIPMENT (586)949-3320



Heavy Duty Dual Lances

- 1/8" zinc plated steel pipe
- 10.5 GPM maximum
- 3000 PSI maximum
- 284° F. maximum



4193

Part	Product
1696	36" Dual lance
4193	36" Deluxified dual lance
1697	72" Dual lance
4393	72" Deluxified dual lance
3112	O-ring & seat repair kit
4331	10007270 Brass Nipple
3117	10007366 shutter
5829	Rubber handle

Stainless Steel Dual Lances

Deluxified lances equipped with socket on high pressure outlet and soap nozzle on low pressure outlet and QC plug on inlet



- 10.5 GPM maximum
- 4100 PSI maximum
- 302°F. maximum
- Nozzle protectors standard
- 1/4" stainless steel tubes



Part	Product
3476	40" MTM Dual lance
4502	MTM Deluxified lance
4582	Valve repair kit



- 10.5 GPM maximum
- 3650 PSI maximum
- 302°F. maximum
- Nozzle protectors standard
- 1/4" stainless steel tubes



Part	Product
6846	40" AL344LS
6847	AL344LS Deluxified
4840	Valve & handle repair kit

Flexible Wands

Ideal for washing vehicle wheel areas in car wash.



- 1/4" MPT inlet & outlet
- 2250 PSI maximum
- 10 GPM maximum

Part	Product
4411	18" Black
6793	18" Blue
3342	24" Black

SPRAY-FLEX



Work more efficiently, with more control in greater comfort. Increase job safety while cutting waste and time on the work site. Spray Flex adjusts up to 90 degrees and holds its shape up to 5000 PSI. 1/4" FPT x 1/4" MPT

Part	Product
4598	Spray flex 3000
4599	Spray flex 5000

Steam Guns

Built for the toughest cleaning situations! Handle the heat and don't lose pressure!

Gun valve bodies are stainless steel to resist chemical erosion. handles are zinc plated for rust prevention. Weivels reduce fatigue by preventing the operator from fighting the heavy steam hose and by allowing the rotation of spray head up under difficult areas, such as inside tanks.



3183

Has a lever steam valve and hose swivel. 1/2" inlet



3186

Has lever steam valve and both a barrel and hose swivel. 1/2" inlet



3184

Open gun with barrel swivel. 1/2" inlet

Grip and barrel made of schedule 80 steel. Dissipates heat through mounting springs and vented construction



3187



3185

Economical open gun option with barrel and air cooled grip

Part	Model
3183	Lever control gun swivel outlet
3186	Lever control gun swivel in/out
3184	Open steam gun
3187	Barrel & Grip 36" long
3185	Open Single Piece Gun 44"
4059	Swivel repair
4060	Valve repair

RP RABINE EQUIPMENT (586)949-3320

Fan Steam Nozzle

Part	Size
3054	Flat nozzle 1/4" FPT



Round Steam Nozzle

The larger the nozzle size, the smaller the orifice, thereby increasing the pressure

Orifice number is drill size

Part	Size
3002	Round blank 3/8" mpt
3205	#16 orifice round nozzle
3317	#30 orifice round nozzle
3207	#32 orifice round nozzle
3209	#36 orifice round nozzle
3318	#42 orifice round nozzle
3210	#48 orifice round nozzle
3211	#50 orifice round nozzle



Telescopic Wand Optional Accessories:


Gutter Cleaning Made Easy

Blast dirt leaves and other debris from gutters without a ladder. HPC gutter cleaning attachment is angled for direct spray in gutters and down spouts. Attaches in seconds to 22mm coupler on pole.



Part	Product
6739	Gutter kit

McCauley Sprayflex attachment for hard to reach areas, which would normally need a ladder.



Part	Product
6738	Sprayflex kit

When additional agitation is required for cleaning high areas, the low pressure brush is ideal. Attaches in seconds to 22mm screw coupler on telescopic pole.



Part	Product
5005	Brush kit

Telescopic Super Wands

HPC telescopic wands help to make the most difficult of cleaning jobs easier. The poles feature thick walled fiberglass and aluminum to withstand the rigors of everyday usage by the professional. The hose, gun and nozzles are designed for easy replacement in the field if necessary.



Features:

3/8" R1 4000 PSI hose to reduce overall weight
Heavy duty linear spray gun
Quick connect nozzle attacher
Stops on each pole prevents sections from pulling apart.

Save Freight Charges Order 2 at a Time!

The telescopes are considered oversized. 24' Ships at 70 lbs. Smaller poles ship at regular weight plus UPS additional handling charge.

Part	Product
6762	4' to 12' 3 section
6178	6' to 18' 3 section
6182	8' to 24' 3 section
6181	4'-12' replacement pole
6130	6'-18' replacement pole
6270	8'-24' replacement pole
5360	Plastic spray gun attacher
5361	Plastic nozzle attacher
6050	35mm Large collet & nut
6095	28mm middle collet & nut
6196	Replacement hose 12' pole
6183	Replacement hose 18' pole
6176	Replacement hose 24' pole
2396	ST-601 linear spray gun

Anti-fatigue Strap & Belt

Reduce the strain of holding a telescopic wand for extended periods of time.



Part	Product
4025	Belt (comes with clamp)
4925	Pole Clamp

Telescopic Wands